SG 2360



PRODUCT INFORMATION

- ***Operation:*** *motorised*
- ***Range:*** *S - L*
- ***Fitting:*** *ceiling, wall*
- ***Colours:*** *white RAL 9016, black 9005*
- ***Fabrics:*** *refer to Silent Gliss fabric collection*

Features:

- *Quiet motors*
- *Soft stop*
- *Various control options*
- *Enclosed headrail*
- *Fascia included*

04/2026/V1

SilentGliss

SYSTEM SPECIFICATIONS

A. SYSTEM DIMENSIONS

4 m



*60 cm**
**see motor specification table*



4 m

16 m²

10 kg

B. PROFILE

Profile information



SG 2371
Head box



SG 2372
Tube ø 45 mm



SG 11434
Box cover



SG 2004
Bottom bar 20x7 mm



SG 2006
Bottom bar 28x3 mm



SG 2135
Rod steel ø 3 mm



SG 2137
Rod fiberglass ø 4 mm



SG 2144
Profile ø 8 mm

C. HOW TO MEASURE



A: System width
B: System height

FITTING

A. FITTING INFORMATION

For detailed fitting information, visit the Silent Gliss website.

Fixing points



B. CEILING FITTING

Clamp SG 3003





SG 3003
Clamp

Bracket SG 2521





SG 2521
Bracket

C. WALL FITTING

Smart Fix



Smart Fix SG 11200 - SG 11204 and bracket SG 2521:
Screw SG 10395 (M4x6) needed.



Square Smart Fix SG 11210 - SG 11214 and bracket SG 2521:
Screw SG 10395 (M4x6) needed.



Universal Smart Fix SG 11154 - SG 11156 and bracket SG 2521:
Screw SG 10492 (M4x8) needed.

Smart Fix	*X mm*
SG 11200 / SG 11210	*80-84*
SG 11201 / SG 11211	*100-104*
SG 11202 / SG 11212	*120-124*
SG 11203 / SG 11213	*140-144*
SG 11204 / SG 11214	*170-174*
SG 11154	*134-162*
SG 11155	*164-192*
SG 11156	*214-242*



SG 2521
Bracket

SG 10395
Pan head screw M4x6

SG 10492
Pan head screw M4x8



SG 11200
Smart Fix 60 mm



SG 11201

Smart Fix 80 mm



SG 11202

Smart Fix 100 mm



SG 11203

Smart Fix 120 mm



SG 11204

Smart Fix 150 mm



SG 11210

Square Smart Fix 60 mm



SG 11211

Square Smart Fix 80 mm



SG 11212

Square Smart Fix 100 mm



SG 11213

Square Smart Fix 120 mm



SG 11214

Square Smart Fix 150 mm



SG 11154

Universal Smart Fix 120 mm



SG 11155

Universal Smart Fix 150 mm



SG 11156

Universal Smart Fix 200 mm

Bracket SG 2363





SG 2363

Bracket 68 mm

D. FITTING WITH SIDE GUIDE OPTION







SG 2384



SG 8235

Side guide wire base short



SG 8236

Side guide wire base long



SG 8237

Side guide wire holder



SG 8249

Side guide device



SG 10643

Side guide wire ø 1.3 mm x 4.2 m

SYSTEM OPTIONS

A. FABRIC MAKE-UP



Type A (standard)

A: Loop tape SG 3074
B: Cord SG 2216
C: Child safety hook set SG 3164
D: Hollow hem
E: Bottom bar SG 2004
F: Child safety: max. distance 200 mm



Type B (rod)

A: Hollow hem
B: Child safety eyelet hard fold SG 3069
C: Rod SG 2135
D: Cord SG 2216
E: Child safety hook set SG 3164



Type C (rod)

A: Child safety eyelet set SG 3161
B: Rod SG 2135 / SG 2137
C: Cord SG 2216
D: Child safety hook set SG 3164
E: Option: Rod SG 2135 / SG 2137 can be installed to room side

B. SIDE GUIDES



Additional parts:

- *2x SG 2384 Side guide wire holder*
- *2x SG 8235 / SG 8236 Side guide wire base short / long*
- *2x SG 8237 Side guide wire holder*
- *2x SG 8249 Side guide device*
- *2x SG 10643 Side guide wire ø 1.3 mm*

Note:

- *Up to 15° from vertical*

MOTORS & CONTROLS

A. MOTOR FEATURES

Motors	50-Series	40-Series	25-Series	20-Series	5-Series
	SG 11251	SG 11943 SG 11944	SG 11625	SG 10522	SG 10715
Motor Features					
Soft stop	●	●	●	●	
Electronic end-stop	●	●	●	●	
Electronic revolution counter (unlimited revolution)	●	●	●	●	
Mechanical end-stop					●
Mechanical revolution counter (limited revolution)					●
One intermediate position possible		●			
Bottom bar allignment	●	●			
Noiseless stop				●	
Parallel wiring possible without additional relays		●	●	●	
Disconnectable motor cable	●	●	●	●	
IP class	IP 30	IP 30	IP 30	IP 44	IP 44
Control Features					
Mains power control			●	●	●
Dry contact control	●	●			
Dry contact and / or SG Control N control		●			
SG Control N (built-in receiver)		●			
Smart by Silent Gliss	●				
Suitable for most major home automation systems (with suitable interface)		●	●	●	●

B. MOTOR SPECIFICATIONS

Motors	Max. weight	Min. system width	Voltage	Current	Frequency	Speed	Frequency receiver
50-Series (Smart by Silent Gliss)							
SG 11251	10 kg	60 cm	24 V DC	1.5 A	n/a	32 rpm	n/a
40-Series							
SG 11943	10 kg	83 cm	100-240 V AC	0.6 A	50-60 Hz	32 rpm	433 MHz
SG 11944	10 kg	60 cm	24 V DC	1.5 A	n/a	32 rpm	433 MHz
25-Series							
SG 11625	10 kg	87 cm	100-240 V AC	0.8 A	50-60 Hz	32rpm	n/a
20-Series							
SG 10522 (standard)	10 kg	60 cm	230 V AC	0.6 A	50 Hz	30 rpm	n/a
5-Series							
SG 10715	10 kg	60 cm	230 V AC	0.5 A	50 Hz	28 rpm	n/a

C. OPERATING METHODS

See catalogue "controls" for details.

Wall Switch

System can be operated by fixed wall switch.

SG Control N

Various radio hand-held and wall transmitters available.

Silent Gliss Move App.

Smart by Silent Gliss

Open designed two-way communication system which allows to flawlessly integrate products with most major building management systems.

D. WIRING DIAGRAMS

Refer to Silent Gliss website.

PARTS

A. STANDARD PARTS

SG 2004

Bottom bar 20x7 mm

SG 2216

Cord ø 0.85 mm



SG 2221

Velcro tape



SG 2371

Head box

SG 2372

Tube ø 45 mm



SG 2373

End cover

SG 2374

End cover



SG 2375

Tube adapter ø 43 mm

SG 2376

Shell

SG 2377

Pin

SG 2381

Motor plate

SG 2539

Tape



SG 3003

Clamp



SG 3164

Child safety hook set



SG 9917

Hirschmann portable socket-outlet STAK 3 N

SG 10284

O-Ring

SG 10522

Motor 230V AC, 20-Series S 3/30

SG 10621

Tube adapter



SG 11185

Pan head screw 2.2x9.5 DIN 7981 C

SG 11324

PT Screw Countersunk KA35x14



SG 11354

Motor drive 10/20-Series

SG 11434

Box cover

B. OPTIONAL PARTS

SG 2006

Bottom bar 28x3 mm



SG 2093

Ring



SG 2135

Rod steel ø 3 mm



SG 2137

Rod fiberglass ø 4 mm



SG 2144

Profile ø 8 mm



SG 2164

Ring tape



SG 2363

Bracket 68 mm



SG 2378

Support

SG 2379

Sleeve



SG 2384



SG 2521

Bracket



SG 3055

Hook

SG 3069

Child safety eyelet



SG 3074

Loop tape



SG 3161

Child safety eyelet set



SG 3165

Child safety eyelet set

SG 3166

Child safety tape set

SG 8235

Side guide wire base short

SG 8236

Side guide wire base long



SG 8237

Side guide wire holder



SG 8249

Side guide device

SG 8943

Cable grommet



SG 9916

Hirschmann plug set



SG 9959

Central control unit relay



SG 10149

Pan head screw 2.2x6.5



SG 10293

Cable 230V AC, 2/3/5/10 m

SG 10395

Pan head screw M4x6



SG 10492

Pan head screw M4x8



SG 10643

Side guide wire ø 1.3 mm x 4.2 m

SG 10715

Tubular motor 230V AC, 5 Series S 6/28



SG 11154

Universal Smart Fix 120 mm



SG 11155

Universal Smart Fix 150 mm



SG 11156

Universal Smart Fix 200 mm



SG 11200

Smart Fix 60 mm



SG 11201

Smart Fix 80 mm



SG 11202

Smart Fix 100 mm



SG 11203

Smart Fix 120 mm



SG 11204

Smart Fix 150 mm



SG 11210

Square Smart Fix 60 mm



SG 11211

Square Smart Fix 80 mm



SG 11212

Square Smart Fix 100 mm



SG 11213

Square Smart Fix 120 mm



SG 11214

Square Smart Fix 150 mm

SG 11251

Motor 24V DC, 50-Series S 3/32



SG 11260

Gateway Cedia



SG 11261

Gateway KNX



SG 11262

Expansion unit



SG 11263

Power supply 24V DC, 2.5A DIN Rail



SG 11264

Power supply 24V DC, 3.8A DIN Rail



SG 11265

Power supply 24V DC, 5A DIN Rail



SG 11266

Power supply 24V DC, 10A DIN Rail



SG 11355

Motor drive 5-Series



SG 11356

Motor drive 40/50-Series



SG 11482

Ring

SG 11625

Motor 100-240V AC, 25-Series S 3/32



SG 11900

Move Server



SG 11931

Radio hand held 1 channel



SG 11932

Radio hand held 6 channel

SG 11936

Radio wall transmitter 1 channel

SG 11937

Radio wall transmitter 6 channel

SG 11943

Motor 100-240V AC, 40-Series S 3/32, radio receiver

SG 11944

Motor 24V DC, 40-Series S 3/32, radio receiver



SG 11965

Power supply set 24V/2A with EU/ CH plug